Boulevard











Construction	Tufted Cut Pile Carpet
Yarn	100% Solution Dyed Nylon
Width	4.0m
Standard Roll Length	30m
Yarn Weight	50oz/yd²
Pile Height	14.0mm
Total Thickness	16.0mm
Machine Gauge	1/8th
Primary Backing	Woven Polypropylene
Secondary Backing	Action Fleece
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	AS ISO 9239-1
VOC Rating	Pass
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential Light Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential Warranty 3 Year Commercial Warranty
Installation	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001



- $\bullet \ \ \text{For samples, range and warranty details please contact us on +61\,7\,5415\,1134\,or\,belgotex.com.au}$
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex[®]

A world of perfect choices_

belgotex.com.au 13/08/2024