

Stream



| | |
|-----------------------------------|--|
| Construction | Structured Loop Pile Carpet Tile |
| Yarn | 100% Regenerated Econyl Nylon |
| Size | 500mm x 500mm |
| Tiles per Carton | 20pcs / 5.0m ² |
| Pile Weight | 770g/m ² |
| Total Weight | 4365g/m ² |
| Pile Height | 3.4mm |
| Total Thickness | 6.8mm |
| Machine Gauge | 1/12th |
| Backing | Bitumen |
| Electrical Properties | Antistatic |
| Electrical Propensity | ≤ 2kV |
| Fire Rating | Bfl-s1 (EN 13501) |
| VOC Rating | A+ (AGBB protocol and GUT label) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Acoustic Insulation | ΔLw 25dB (ISO 140-8) |
| Acoustic Absorption | α _w 0.20 (ISO 11654) |
| Dimensional Stability | <0.20% (EN986) |
| Thermal Insulation | <0.15m ² C°/W |
| Underfloor Heating | Suitable |
| Colour Fastness | 5-6/8 on Grey Scale (ISO105-B02) |
| Luxury Class | LC2 |
| Rating | Heavy Duty Commercial |
| Stair Rating | Suitable |
| Warranties | 5 Year Commercial Warranty |
| Installation | Laying recommendation: Monolithic or Brick. Must be laid in accordance with AS/NZ Installation Standards. |
| Environmental | GUT Label LEED® BREEAM Greenstar CRI Green Label Certified Low VOC, Contains recycled fibre Environmental Product Declaration Quality Management ISO 9001 Environmental Management ISO 14001 |



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of
perfect choices_