

# Terrain



<b>Construction</b>	Patterned Tufted Loop Pile Carpet Tile
<b>Yarn</b>	100% Stainproof SDX (Solution Dyed Nylon)
<b>Size</b>	1000mm x 250mm
<b>Pile Weight</b>	475g/m <sup>2</sup>
<b>Tiles per Carton</b>	20pcs / 5.0m <sup>2</sup>
<b>Pile Height</b>	3.0mm
<b>Total Thickness</b>	5.0mm
<b>Machine Gauge</b>	1/10th
<b>Backing</b>	Flexbac
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	< 2kV (ISO 6356 & EN 1307)
<b>Fire Rating</b>	CRF 9.1kW/m <sup>2</sup> (BSEN 13238:2010)
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Acoustic Absorption</b>	$\alpha_w$ 0.15 (ISO 354)
<b>Underfloor Heating</b>	Suitable
<b>VOC Rating</b>	Pass (GBCSA/GLP Criteria)
<b>Classification</b>	Heavy Duty Commercial
<b>Stair Rating</b>	Suitable
<b>Warranty</b>	15 Year Commercial Warranty
<b>Installation</b>	Laying recommendation: Parquet or Brick. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	GreenStar Low VOC, solution dying uses no water Environmental Management ISO 14001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width  $\pm 3$ mm, Pile Weight  $\pm 5$ %.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A world of perfect choices\_