

Category	Hardened Timber
Type	100% Real Wood - Oak
Plank Size	151mm x 2000mm
Planks per Carton	7pcs / 2.1m ²
Weight per Carton	11.0kg
Thickness	9.2mm
Top Layer Thickness	0.6mm
Surface Finishing	Pro Matt Lacquer
Core	Ultra HDF
Locking System	Välinge 5G Dry
Slip Resistance	P3 (AS 4586-2013 Appendix A)
Thermal Resistance - plank only	0.075 m ² K/W (EN 12667)
Thermal Resistance - with Aqua Elite underlay	0.148 m ² K/W (EN 12667)
Thickness Swelling	<10% (EN 14354)
Fire Rating	CRF 8.0 kW/m ² , Smoke 16.46 %.min (AS ISO 9239-1)
Indoor Air Quality	A+ Emissions / Indoor Air Comfort Gold®
Formaldehyde Emissions	<0.005 ppm, E1 (EN 717-1)
Wear Resistance	>6000 cycles (EN 14354)
Impact Resistance	EC3 (EN 14354)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Classification	Class 23 Domestic Heavy Class 33 Commercial Heavy
Stair Rating	Suitable
Warranties	35 Year Residential Warranty 15 Year Moisture Protection (Kitchen, Laundry, Toilet) Commercial on Request
Installation	Must be properly installed according to the installation instructions.
Environmental	Forest Stewardship Council (FSC) Nordic Swan Ecolabel Certified GREENGUARD Gold Certified Quality Management ISO 9001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber-based materials should not be left in contact with the floor for prolonged periods as they may cause tattooing or permanent staining on the lacquered surface. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.

Belgotex®

A world of perfect choices_