

Grand Prix

Construction	Needlepunch Carpet
Yarn	100% Polypropylene Stainproof Miracle Fibre
Width	3.0m
Standard Roll Length	40m
Total Weight	800g/m ²
Total Thickness	5.7mm
Backing	Resinbac
Electrical Properties	Antistatic
Fire Rating	CRF 4.3kW/m ² (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew
Colour Fastness	7
Use	Indoor
Rating	Commercial
Stair Rating	Suitable
Installation	It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified Low VOC, Solution dying uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ± 3 mm, Pile Weight $\pm 5\%$.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of
perfect choices_