

Grid - ProBac



Construction	Patterned Tufted Loop Pile Carpet Tile
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	500mm x 500mm
Pile Weight	475g/m ²
Tiles per Carton	20pcs / 5.0m ²
Pile Height	2.0mm
Total Thickness	5.0mm ± 0.5%
Machine Gauge	1/10th
Backing	ProBac
Electrical Properties	Antistatic
Impact Sound Reduction	ΔLw 27 dB (AS ISO 717.2)
Sound Absorption Coefficient	αw 0.25 (ISO 11654)
Thermal Resistance	0.1253 m ² K/W
Dimensional Stability	<0.20% (EN 986)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
VOC Rating	Pass (GBCA Criteria)
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Installation	Laying recommendation: Quarter Turn. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Eco-Wash™ Treatment Low VOC, solution dyeing uses no water Occupational Health and Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of perfect choices_