

# Storm II



Construction	Tufted Multi Scroll Loop Pile Carpet Tile
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	500mm x 500mm
Pile Weight	550g/m <sup>2</sup>
Tiles per Carton	20pcs / 5.0m <sup>2</sup>
Pile Height	6.0mm
Total Thickness	7.0mm
Machine Gauge	1/10th
Backing	Flexbac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Fire Rating	CRF 7.2kW/m <sup>2</sup> (ISO 9239-1)
VOC Rating	Pass (GBCSA/GLP Criteria)
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Installation	Laying recommendation: Quarter Turn. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greenstar Low VOC, solution dying uses no water, Eco-Wash™ Treatment Occupational Health and Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or [belgotex.com.au](http://belgotex.com.au)
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

A world of  
perfect choices\_