Sumptuous











Construction	Tufted Cut Pile Carpet
Yarn	100% Premium Soft Solution Dyed Nylon
Width	4.0m
Standard Roll Length	25m
Yarn Weight	46oz/yd²
Pile Height	10.0mm
Total Thickness	12.0mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1815 / ISO 6356)
Fire Rating	CRF 4.5kW/m² (ISO 9239-1)
VOC Rating	Pass (GBCSA/GLP Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable - Maximum Temperature 37°C
Rating	Extra Heavy Duty Residential Medium Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential Warranty 7 Year Commercial Warranty
Installation	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified Greenstar Low VOC, solution dying uses no water, Eco-Wash™ Treatment Occupational Health and Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001





- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex[®]

A world of perfect choices_

belgotex.com.au 27/02/2024